

Castrol EDGE 10W-60

Strength to Perform - Freedom to Drive

Description

Castrol EDGE with *Fluid Strength Technology*TM is Castrol's strongest and most advanced range of engine oils. Its unique adaptive strength reduces metal to metal contact across a range of different driving speeds.

Castrol EDGE - lowers friction and maximises engine performance.

Castrol EDGE 10W-60 gives you the confidence to demand maximum engine performance in older sports cars, competition and the latest technology engines which often operate under higher pressures requiring an oil with unsurpassed strength and performance credentials.

Castrol EDGE 10W-60 is proven in tests to deliver outstanding oil strength.

A new technology that has the adaptive strength to respond to your engine's every need.

Castrol EDGE. Strength to Perform - Freedom to Drive.

Application

Castrol EDGE 10W-60 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA A3/B4, A3/B3, API SM/CF or earlier specification 10W-60 lubricant.

Castrol EDGE 10W-60 has exclusive approval for BMW M-Models



Advantages

Castrol EDGE 10W-60:

- Delivers and sustains maximum horsepower for longer, even when under pressure
- Protects short and long term engine performance
- Ensures maximum protection under all driving conditions, speeds and temperatures
- Reduces engine deposits to help maximise engine response
- Recommended by BMW for M models

Typical Characteristics

Name	Method	Units	Castrol EDGE 10W-60
Density @ 15°C, Relative	ASTM D4052	g/ml	0.853
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	22.7
Viscosity, CCS -25°C (10W)	ASTM D5293	mPa.s (cP)	4879
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	160
Viscosity Index	ASTM D2270	None	173
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	203
Ash, Sulphated	ASTM D874	% wt	1.29

Product Performance Claims

ACEA A3/B3, A3/B4

API SM/CF

BMW Exclusive approval for BMW M-Models

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE 10W-60

27 Jul 2011

Castrol, EDGE 10W-60 and the Castrol logo are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol UK Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire, SN3 1RE, Castrol (Ireland), Castrol Ireland Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire, SN3 1RE

Castrol UK Telephone: 01793 512712 Automotive Technical Helpline: 0845 082 1719 Orders/Enquiries: 0845 6008125 Castrol Ireland Telephone: +44 (0)1793 512712 Automotive Technical Helpline: 1800 509 353 Orders/Enquiries: 1850 930 394

www.castrol.com/uk

Page 2 of 2